

## Andhra Pradesh State Road Transport Corporation Office of the Managing Director, Bus Bhavan, Hyderabad - 500 624.

No: OP4/760(oils)/2011-MED

## CIRCULAR No.05/2013-MED, Dt.01.02.2013

Sub: <u>LUBRICATING OILS</u> - Introduction of new Engine oil API CI4 plus SAE 15w40 oil with enhanced oil drain period for Tata Cummins ISBe Engines - Instructions communicated - Reg.

Ref: Tata Service Circular No.SC/2012/34, Oct-2012

Hitherto, the Tata vehicles fitted with Cummins ISBe engines (1624 RELE) are being filled with SAE15w40 API CI-4 grade engine oil with drain period of 18,000 kms.

M/s Tata Motors Ltd have recently communicated through their Service circular cited that they have enhanced the engine oil change period for vehicles fitted with *Cummins ISBe* engines to *40,000 kms for City applications* by using the following recommend grade oils.

Engine	Application	Drain Interval	Oil recommended
ISBe Cummins Engine BS III / BS IV	Long Distance (Mofussil)	Initial drain: 40,000 Kms Subsequent: 60,000 Kms (or) One year which ever expires earlier	1) CASTROL RX SUPER TURBO 15W40 (CI4 PLUS 2) MAK TATA MOTORS CI4
	Short Distance (City)	Initial drain: 20,000 kms Subsequent: 40,000 kms (or) One year which ever expires earlier	PLUS 15W40 of M/s BPCL  3) SHELL RIMULA T4 15W40 CI4 PLUS

The Field Managers & Mechanical Supervisors are advised to make note of the above modifications and implement the revised guidelines accordingly.

The Controllers of Stores are advised to procure & supply the above engine oil to the Depots based on the requirement from respective Dy.CMEs.

EXECUTIVE DIRECTOR(E&!T

To

The Depot Managers of Greater Hyderabad zone & VSP City Divn for necessary action.

Copy to: ED (A&P) & ED(GHZ&HZ) for infn.

Copy to: RMs HCR & SCR for necessary action

Copy to: CME (O), CCOS, CME(C&B), CE (IT), CM (HRD) for information

Copy to: DyCME (O), DyCME (P), DyCME(C&B), DyCME (IED), CSTO, COS(C) | & || for information.

Copy to: DyCMEs HYD, SD, CRMR SNG, WM/UPL, COS/UPL & DY.CAO/GHZ for N.a.

Copy to: All Principals of ZSTCs, BTC, HPT & TA/HPT for information.

Copy to: Maintenance In-charges GHZ depots for necessary action.

Copy to: manual section.